



ASELSWITCH | INDR

aselsan

INDUSTRIAL TYPE ROUTING
DEVICES

#InformationTechnologies



aselsan

INDUSTRIAL TYPE ROUTING DEVICES

The aselSWITCH IndR router family consists of layer 3 network devices designed to meet IPv4/IPv6 communication needs at industrial standards, with routing capabilities ranging from 96GBits - 300 GBits.

The product family ranges from 8 to 48 ports, available in various sizes and capacities. known for ease of installation and operation, the product family excels in providing robust networking solutions.

General Properties

- 19-inch rack compatibility
- Ability to be powered from the city grid or an external AC energy source
- Fanless design
- IEEE 802.3at PoE/PoE+ support
- At least 4.5Mpps packet processing and routing performance for 64 Byte packets
- Wirespeed operation
- All kinds of network topologies (mesh, star, ring, line, tree etc.) can be created with the devices and there is no interruption or deficiency in the service to be provided in the system
- IPv4 and IPv6 protocol support and STANAG 5067 compatibility
- Ease of management with SNMO
- Ability to configure from USB interface
- All ports on the devices can work non-blocking

Physical Properties

- Industrial type operating temperature; -40°C +70°C (IEC 60068)
- Industrial type storage temperature; -40°C +70°C (IEC 60068)
- Industrial type humidity; %10 - %95 @+40°C (IEC 60068)
- Industrial type IP protection; IP30
- Industrial type vibration, free fall, shock resistance (IEC 60068)
- Industrial type EMI-EMC compatibility (FCC Class A CE/EN61000)
- Safety (CE/EN 60950-1)
- Max. operating altitude; 3000m

Remote Configuration Abilities

- SNMP v2, v3
- Web-based management (HTTP, HTTPS)
- RS232 serial console management
- Telnet, SSH

Device Interfaces

- Ethernet/SFP : 8 – 48 x 10/100/1000Base-T
2 – 4 x SFP/SFP+
Auto-negotiation
Auto MDI/MDIX
- MNG : 1 x 10/100/1000Base-T ethernet management port
- USB : 1 x USB 3.0 interface
- CLI : 1 x 115.2KBits console interface

Power Supply

- Supply : AC and DC, seamless automatic switching
- Input : 110 VAC / 220 VAC ± %10
50 Hz ± %5 / 60 Hz ± %5 24 VDC

Maintenance

- Built-in test - BIT (first boot test, user BIT, continuous BIT)

Supported Protocols

- Routing protocols : Static routing
RIP v1/v2
EIGRP
OSPF v2/v3
BGP
IS-IS
- Layer 2 VPN : L2TPv3
- Layer 3 VPN : GRE MPLS
- Multicast (IGMPv3, MLDv2, MSDP, PIM: SM, SSM, DM)
- QoS (DiffServ, STANAG 4711 and STANAG 4644 compatibility)
- Network security tools : IPsec ACL
- Network manager tools : NAT
DHCP
ICMP
DNS
Port mirroring
NTP server and client
- Authorization tools : RADIUS
TACACS+