



ASTELA | SK 4940

aselsan

SK2 MISSION CRITICAL REPEATER

#PublicSafetyCommunication



aselsan



SK2 MISSION CRITICAL REPEATER

The ASTELA SK4940 Repeater is a repeater radio with many scenarios in public safety communication.

Multiple Operation Modes

SK4940 operates with high output power. It receives and transmits analog, digital clear or digital encrypted signals transparently. Repeater radio has Linux operating system.

ASTELA SK4940 operates as Mobile Repeater Transceiver which creates local coverage for radio users or becomes a component of radio communication system as a Fixed Repeater. It can be used in ASELSAN BiGA SK2 radio communication system as analogue and digital.

Resilience to Severe Environmental Conditions

Institutions in charge of public safety may need to use these radios in challenging environments such as very high or very low temperature, high humidity, low pressure and dust. ASTELA SK4940 is designed by considering these requirements and supports MIL STD 810E standards.

Technical Specifications

Frequency	: 136-174 MHz (VHF) or 380-470 MHz (UHF)
Sensitivity	: ≤ -119 dBm
BER	: $\leq 0.1\%$
Rf power output (dual band)	: 10-40 W (VHF) 10-30 W (UHF)
Rf power output (single band)	: 10-90 W (VHF) or 10-70 W (UHF)
Frequency accuracy	: ≤ 0.5 ppm
Weight	: 2425 g
Dimensions	: 61x 177 x 246 mm
Operating temp. range	: $30^{\circ}\text{C} / +60^{\circ}\text{C}$
Storage temp. range	: $-40^{\circ}\text{C} / +85^{\circ}\text{C}$
Humidity	: 90%, $+50^{\circ}\text{C}$
Power supply	: 13.6VDC $\pm 20\%$ or 90-264 Vac, 50 Hz
Operating system	: Linux

Standards and Certificates

LVD	: EN 60950, IEC 62368 (2014/35/EU directive)
EMC	: EN 301 489-1, EN 55032 (2014/30/EU directive)
Digital	: ETSI EN 300 113
Analog	: ETSI EN 300 086
High temperature	: MIL-STD-810G M 501.6 Pro I Cat A1, Pro II cat A1
Low temperature	: MIL-STD-810G M 502.6 Pro I Cat C2, Pro II cat C1

Specifications are subject to change without any notice. | All tolerances are within $\pm 10\%$.