

aselsan

EKS-2136B-IR

FACE DETECTION CAMERA

36X OPTIC / 12X DIGITAL ZOOM
EXCEPTIONAL LIGHT SENSITIVITY
IP66/IK10 PROTECTION
IR LED ILLUMINATION
WIDE DYNAMIC RANGE
IMAGE NOISE REDUCTION
AUTOMATIC IMAGE STABILIZATION
7/24 LIVE STREAM



EKS-2136B-IR

FACE DETECTION CAMERA

Camera

Sensor Type & Size	½ inch FHD CMOS
Highest Resolution	1920x1080, 25FPS (2MP)
Adjustable Resolution	1080p/720p/480p
Mechanical IR Cut Filter	Available
Adjustable IR Illumination	Integrated IR LED's
SD Card Support	Available (128GB)
Light Sensitivity(F1.5)	0.005Lux (Color), 0.0005Lux (Black/White)
Shutter	1/1 - 1/10000
Focus Mode (AF)	Automatic/Manual
Exposure Mode (AGC)	Automatic/Manual
White Balance Mode (AWB)	Automatic/Manual
Image Stabilization (EIS)	Available
Wide Dynamic Range (WDR)	Available
3D Image Noise Reduction (3DNR)	Available
Back Light Compensation (BLC)	Available

Lens

Lens Type	Varifocal
Focal Length	5.8mm-210mm
Horizontal Field of View	2.15°(HTELE) - 58.44°(HWIDE)
Iris	F1.5(TELE) - F4.8(WIDE)
Zoom	36x Optic / 12x Digital

Physical

Operation Temperature	Environmental -30°C ~ +50°C
Liquid Protection Class	IP66
Impact Protection	IK10
Weight	2.75kg

Electrical

Input Power	12VDC /25W
Working Time (Live Stream)	7/24
Audio Input	3,5mm Jack Input and Internal / Speaker/Microphone
Alarm Input/Output	Available