

GÜNGÖR-100

HIGH RESOLUTION DAYLIGHT CAMERA

DEFOG CAPABILITY

CRYSTAL CLEAR IMAGE QUALITY

HD-SDI AND ETHERNET VIDEO OUTPUT

DURABLE AND COMPACT

LONG RANGE DETECTION/RECOGNITION/IDENTIFICATION





GÜNGÖR-100

HIGH RESOLUTION DAYLIGHT CAMERA

Applications

- Long Range Wide Field Surveillance
- Long Range Reconnaissance
- Law Enforcement
- Commercial Military and Security / Surveillance Applications

Main Features

- Continuous Optical Zoom
- Digital X12 Magnification
- Automatic & Manual Focus Adjustment
- Defog Capability
- Image Freeze
- Plug & Play
- Daylight and Near-IR Surveillance
- Suitable for Integrated system Architecture
- Upon Tripod & Pan & Tilt Operation
- Built In Test

Technical Specifications

- Resolution : 1920x1080
- Sensor : 1/2.8" CMOS
- Field of View
 - NFOV : 2.3° (±%10)
 - WFOV : 63.7° (±%10)
- Optical zoom : 30x (Cont.)
- Digital zoom : 12x (Cont.)
- Video Output : HD-SDI, Ethernet
- Remote Control : RS422, Ethernet
- Feed Voltage : 28Vdc
- Weight : <1.6±0.2 kg
- Dimensions : 95.4 x 76.9 x 254.4±1 mm

Environmental Conditions

- Operating Temperature : -32°C, +50°C
- Storage Temperature : -40°C / +60°C
- Standard : MIL-STD-810 G