

GÜNGÖR-2000

RECONNAISSANCE SURVEILLANCE
ELECTRO-OPTIC SYSTEMS

HD-SDI AND ETHERNET VIDEO EXIT

CRYSTAL-CLEAR IMAGE

DURABLE AND COMPACT

LONG DISTANCE RECOGNITION AND IDENTIFICATION

GLOBAL SHUTTER FEATURE

MODULER SYSTEMS MATCH





GÜNGÖR-200D

RECONNAISSANCE SURVEILLANCE ELECTRO-OPTIC SYSTEMS

Application

- Long Distance Reconnaissance and Surveillance
- Sea Defence
- Military Security

General Properties

- Continuous Optic Zoom
- Electronically x4 Magnification
- Push Button-Automatic and Manual Focus Setting
- Automatic and Manual Contrast and Brightness Setting
- Image Freezing
- Plug and Go
- Visible Band Surveillance
- Compatible with Integrated System Architecture
- Ability to test itself
- Runs according to Military Environmental Circumstances Standards

Technical Properties

- Sensor Resolution : 1920x1080
- Sensor : 1/2" CMOS
- Perspective
 - Narrow : 1.5° (±%10)
 - Wide : 30° (±%10)
- Optic Zoom : Continuous, x20 (±%10)
- Electronic Zoom : x2, x4 (Gradual)
- Shutter Feature : Global
- Video Exit : HD-SDI, Ethernet, Composite Analog
- Remote Control : RS422, Ethernet
- Voltage Level : 28 VDC
- Weight : < 6.5 kg
- Dimension (w x l x h) : 133 x 503 x 181 mm.

Environmental Circumstances

- Running Temperature : -32°C / +52°C
- Storing Temperature : -40°C / +63°C
- Environmental Circumstances Std : MIL-STD-810 G, MIL-STD-461F

