

RNE-410

RADIO NAVIGATION EQUIPMENT

DO-178C AND DO-254 CERTIFIABLE





RNE-410

RADIO NAVIGATION EQUIPMENT

Radio Navigation Equipment (RNE-410) is an indigenously developed navigation unit that is designed to operate both in civil and military aerial platforms.

RNE-410 is composed of VHF Omni-Directional Range (VOR), Instrument Landing System (ILS), Glideslope (GS), Marker Beacon (MB) and Automatic Direction Finder (ADF) Radio Transceivers.

RNE's functional capabilities and its modular architecture provide integration to various fixed-wing and rotary-wing platforms easily.

General Specifications

- VOR Receiver Function (ETSO-2C40/TSO-C40 compatible)
- ILS Receiver Function (ETSO-2C36/TSO-C36 compatible)
- ILS GS Receiver Function (ETSO-2C34/TSO-C34 compatible)
- MB Receiver Function (ETSO-2C35/TSO-C35 compatible)
- ADF Receiver Function (ETSO-2C41/TSO-C41 compatible)

Interfaces

- ARINC-429 Input / Output Interface
- MIL-STD-1553B Interface
- Discrete Input / Output Interface
- Audio Interface
- Maintenance Interface

Physical Specifications

- Dimensions : 91 mm (W) x 132 mm (H) x 296 mm (D)
- Weight : < 3 kg (including mounting tray)

Power Interface

- Operating Voltage : 28 V (Nominal)
- Power Consumption : 26 W (Nominal)

Environmental Conditions

- Operating Temperature and Altitude: -55°C / +70°C, 55.000 ft
- Storage Temperature: -55°C / +85°C

Qualifications

- MIL-STD-810G
- MIL-STD-704F
- DO-160G